



Mirage™ is manufactured by Autex Industries Ltd and Autex Australia Pty Ltd under an ISO 9001 and ISO 14001 certified Quality and Environmental Management Systems. The product is guaranteed to be free from manufacturing defects and carries a Manufacturer's Guarantee for a period of no less than ten years to meet all of the performance properties stated within this guarantee.

**Specification**

**Product name** Mirage™  
**Description** 100% polyester lightweight semi-rigid panel

	Metric	
Panel Dimensions	1200 mm x 2400 mm	
	1200 mm x 2700 mm	
Tolerance	(+/- 1 mm) x (+/- 1 mm)	
Thickness	12 mm	24 mm
Tolerance	(+/- 6%)	(+/- 6%)

**Physical description/  
properties**

Boiling point:	N/A
Melting point:	250°C
Vapour pressure:	N/A
Specific gravity:	Polyester 1.38
Flash point:	N/A
Explosive limits:	N/A
Solubility in water:	Not soluble
Alkalinity:	pH 7.8
Relative vapour density:	N/A

**Acoustic performance**

Mirage is specifically designed to reduce and control reverberated noise and echo in building interiors. Mirage is made from Cube as the base material.

Minimum Noise Reduction Coefficient 0.45

Frequency (Hz)	125	250	500	1000	2000	4000	NRC
● <b>12 mm Cube</b>	0.05	0.10	0.30	0.65	0.90	0.95	0.45
● <b>12 mm Cube</b> (with 25 mm air gap)	0.05	0.30	0.60	0.95	0.95	0.85	0.70
● <b>24 mm Cube</b>	0.05	0.20	0.60	0.90	1.00	1.00	0.70
● <b>24 mm Cube</b> (with 25 mm air gap)	0.15	0.40	0.85	0.95	0.95	0.95	0.80



## Service

For further information about Mirage or any other Autex Acoustics® product, please contact your account manager or visit our website.

## Care and maintenance

Maintain in accordance with the Care and Maintenance Guide available for this product.

## Product specifications

### Composition

100% polyester fibre from polyethylene terephthalate (PET). Mirage contains a minimum of 80% previously recycled polyester fibre.

### Suitable applications

Partitions, wallcovering with acoustic properties.

### Fire ratings

Mirage is made from Cube as the base material. Cube has been evaluated using the following test methods

### ISO 9705: 1993

Classification: Group 1-S  
Smoke production rate:  
<5.0m<sup>2</sup>/s  
As required by NZBC C/VM2

### AS ISO 9705 - 2003

Classification: Group 1  
(SMOGR<sub>arc</sub>): <100m<sup>2</sup>/s2  
Assessed using methodology AS ISO 9705 - 2003 in accordance with AS 5637:2015, as required by NCC Specification 7: Fire hazard properties S7C4  
FI 4974  
FAR 4055

### BS EN 13501-1:2018

Wall applications  
Classification: B-s1,d0  
(Cube 12 mm)

Tested according to BS EN ISO 11925-2:2020 and BS EN 13823:2020 + A1:2022 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 15102:2019. 7191361939-MEC25/03-JV

### Wall applications

Classification: B-s2,d0  
(Cube 24 mm)

Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 15102:2007 + A1:2011. 7191343095-MEC24/03-JV

### Ceiling applications

Classification: B-s1,d0  
(Cube 12 mm)

Tested according to BS EN ISO 11925-2:2020 and BS EN 13823:2020 + A1:2022 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 15102:2019. 7191361939-MEC25/03-JV

### Ceiling applications

Classification: B-s2,d0  
(Cube 24 mm)

Tested using BS EN ISO 11925-2:2020 and BS EN 13823:2020 and classified in accordance with BS EN 13501-1:2018, as required by BS EN 13964:2014. 7191343095-MEC24/03-JV

### ASTM E-84-15a

Class A, FS:0 - SD:45  
(Cube 1/2")  
RJ4479-2

Class A, FS:0 - SD:65  
(Cube 1")  
RJ4479-1

### Thermal performance

Cube 12 mm R0.30 (@23°C)  
Cube 24 mm R0.60 (@23°C)

### VOC emissions

Autex Acoustics polyester has been tested for chemical emissions in accordance with ASTM D5116 and is considered a low VOC product.  
VOC concentration:  
0.009 mg/m<sup>3</sup> (7 days)

### Water vapour sorption

ASTM C1104 / C1104M-13a  
Test conditions: 49°C, 95%RH  
Water vapour absorbed and adsorped after 4 days:  
0.4% by weight

### Impact resistance

ISO 7892:1988

### Hard body impact

When adhered to 10 mm plasterboard, the system can resist a 9 joule impact without significant damage to Mirage. This is equivalent to the impact of a 0.5 kg object dropped from a 2 m height. A small indentation might be observed when subjected to an impact equivalent to a 0.5 kg object dropped from a 0.5 m height.

### Soft body impact

There is no surface damage or penetration to Mirage when subjected to soft body impacts. When adhered to 10 mm plasterboard, the system can resist a 70 joule impact. This is equivalent to the impact of a 50 kg object dropped from a 150 mm height.

### Microbial resistance

ASTM G21-15  
Growth rating: 0 (No growth)  
Cube does not promote the growth of moulds and mildew.

### Colour fastness to light

Cube is suitable for indoor use only. Light fastness is dependent on use and exposure. Cube has been evaluated to the following standard: ISO 105-B02:2014  
Rating: 6 (Highest = 7)

### Colour fastness to rubbing

ISO 105-X12:2016

Dry rating: 4-5 (Highest = 5)  
Wet rating: 4-5 (Highest = 5)

### Pattern repeat

Non-woven. No pattern repeat from panel to panel, however product has directional grain. Product may vary from samples and batch to batch due to fibre blending and lay-up, which is an inherent feature of this product.

### Fabric care

Blot spills from fabric quickly. Wipe with a damp cloth. Avoid rubbing and excessive amounts of water as this will affect the finish. Use carpet or upholstery shampoo as directed. Blot with a clean dry cloth after each application of solution. Refer to the Autex Acoustics Care and Maintenance Guide for more information.

● **New Zealand**  
702-718 Rosebank Road,  
Private Bag 19988,  
Avondale 1746, Auckland  
T 0800 428 839  
T +64 9 828 9179  
[autexacoustics.co.nz](http://autexacoustics.co.nz)

● **Australia**  
121-131 Global Avenue,  
Essendon Fields,  
VIC 3041  
T 1800 678 160  
T +61 3 9450 6700  
[autexacoustics.com.au](http://autexacoustics.com.au)

● **United Kingdom**  
Unit J4, Lowfields Way,  
Lowfields Business Park,  
Elland, West Yorkshire,  
HX5 9DA  
T +44 0 142 241 8899  
[autexacoustics.co.uk](http://autexacoustics.co.uk)

● **United States**  
742 S Hill Street,  
Suite 501, Los Angeles,  
CA 90014  
T +1 424 203 1813  
[autexacoustics.com](http://autexacoustics.com)

Autex is an ISO certified organisation encompassing Quality (ISO 9001), Environmental (ISO 14001), and Health and Safety (ISO 45001). Brand names and logos are registered or unregistered trademarks owned or used under license by Autex Industries Limited or other members of the Autex Group. © Copyright 2025 Autex Industries Ltd. All rights reserved. It is the user's responsibility to determine if the product and information presented in this document is suitable for the intended application by engaging a suitably qualified consultant. The information contained in this document is correct to the best of our knowledge at the date of its publication. To verify that this document is the most current publication please check our website or contact your Autex Acoustics® account manager.